

国际化文档

产品版本: V1.0 文档版本: 202401

北京有生博大软件股份有限公司

目录

1.	设置语言	3
2. i	语言文件	5
3. (使用	6
4. 7	新增新语言	7

1. 设置语言

1.1. 设置默认语言

在 src/store/modules/settingStore.ts 内更改 webLanguage 的属性值即可设置默认语言:



1.2. 设置可选语言类型

在 src/layouts/componnets/settingsMobile.vue 中更改 webLanguageOptions 数组可以设置国际化的可选语言:

有生云开源文档 | 设置语言



2. 语言文件

在 src/language 目录下可看到语言类型的具体语言文件。

有生云开源文档 | 使用

3. 使用

3.1. vue 文件内使用

	引入插件 vue-i18n 自带的 useI18n, 如下所示:										
×1 6	le <u>E</u> dit Selection <u>V</u> iew O	Go <u>R</u> ur	n Jermin	al <u>Help</u> €-> D'yAvue-kernel-standard	∎⊟08 - a ×						
-m	EXPLORER		V Rela	thonftre use 9- X	8						
9	V Y9VUE-KERNEL-STANDARD		src > v	ions > grantAuthorize > comps > ♥ RelationOrq.vue > () script setup > (#) props > ∯id							
	> dictionary			support (Lunessage, Lunessagesók, Lunditticación) rivoli element-puis ; Lunest (unclasticación) fore / diferención (diferención) ;	$\uparrow \downarrow = \times$						
	> domain			appril (usesercingstone) from g/states approve)	Far-						
	 grantAuthorize 			import { useI18n } from 'vue-I18n';	Signer and a second sec						
	V comps			const { t } = useII8n();	Bistor.						
	▼ RelationOro.vue			const setLingStore = usesetLingStore(); // 注入 法体别障							
	V RelationRole.vue			<pre>const fontSizeOpj: any - inject('sizeObjInfo');</pre>	Sec.						
	V index vue				A CONTRACTOR OF THE OWNER OWNER OF THE OWNER OWNER OWNER OWNER OWNER OWNER OWNER OWNER OWNE						
			100	const props - defineProps((TRANSPORT OF THE OWNER						
	> iconManager		102	10: 0 toos Stelan							
				Cyper so trug, default:							
	> monitor				i il italian						
					State						
•				// (10)日 公至(20)年 白政	With the second second						
	> comps			1/ 300 000 710 and 10	- Form						
	V index.vue										
	> permission			<pre>let currOata - ref(());</pre>							
	> personal										
	v position			// 如於tree定时 	Barrow .						
	✓ comps				and the second s						
	> basemororm				Remonst						
	V pasennovue			const state - reactive([Engrand						
	V personascivoe			// Extloading							
	V index sue			Loading: false, // INTOATE #EE GAPTERE GAPTERE	NE.						
	> resource			1) MacCore Anti Dialantana tablergeonfig: [Northease State						
	> role			columns: [and the second						
	> securityAuditorLog			// (title: '', type: 'selection', fixed: 'left'),	E-						
	> securityUserLog			{ title: computed() -> t(深受), type: 'index', width: 100, fixed: 'left' }, (title: computed() t(河安区) kur: 'compleme'.	Carlos Concernant						
	> sysManagerLog			{ title: $Computed(i) \Rightarrow i("mbxtub"), key: organic" is a complete the interval of the interval$							
	> system			<pre>(title: computed() ⇒ t('號作')), key: 'authorityStr', width: 100 },</pre>							
				{ title: computed(() -> t("提収者")), key: 'authorizer', width: 200 },	A State of the second						
	> userLog			<pre>(title: computed(() -> t('提校的问)), key: 'authorizeTime', width: settingStore.getDateTimeSpan),</pre>	and the second sec						
	♥ Арр.чие			the constat() as triffer()							
				file: coputed() - (tai));							
	TS settings.ts			uidth: 100,	V A						
	\$.env.development			render: (row) -> {							
	\$ vernv.localErnv			return h(
	\$.env.production										
	> OUTLINE			style: {							
£03 -	> TIMEUNE										
	> ITEN ALLY										

3.2. js 或 ts 文件内使用

引入项目自带的 i18n, 如下所示:

×1 1	ile <u>E</u> dit <u>S</u> election <u>V</u> iew <u>G</u> o <u>R</u> un	Jerminal Help		♀ y9vue-kernel-standard		
Ch.		18 dictionaryStore.ts ×				
6	V YYVUE-KERNEL-STA []; E]; O 🗇	src > store > modules > 18 dictionary	Store.ts >			
	> node_modules	1 defineStore }	from 'pinia':) i19n A 2-62	
	> public	2 import 118n from "@/la			7 116h	1 V = X
		<pre>3 const { t } = i18n.glob</pre>	bal;			100
	> api	4 import { listByType, g	etOrgTypeList } from '@/api/dictionary/index';			
	✓ assets	5 import { \$dataType } fi				and a second
	> 655	6 export const usebiction	<pre>naryStore = defineStore('dictionaryStore', {</pre>			1
) inns	/ State: () > (100 C
	> impoun	g dictionary				10 m
) imager	10 booleau	Num: [10 A A A A A A A A A A A A A A A A A A A
	> componente					100 m
	> components		<u>id: 1,</u>			
	 ✓ language () an ison 		name: t("是")			
	tr engon	14				200
	As movely		14.4			Tank Sector
Y	ti jajson		10: 0,			- EBOA
	() zhjson		name: ((Er)			Read and a second second
	> layouts					and the second s
	> router	20 boolea				
	v modules					
	TS dictionaryStore.ts		name: t("是")			
	TS routerStore.ts					
	TS settingStore.ts		14. 6-1			
	TB indexts		name: t/"@")			
	~ theme					
	> blue					
	> dark					
	> default					
	> green		id: 0,			
	global-vars.scss		name: t("女")			
	global.scss					
			14: 1			
			name: t(""")			
	19 directive.ts					
	T8 echarts.ts					Sector Sector
	T8 index.ts	40 userTy	pe: [//人员类型			
	TS object ts					
	13 remixiconData.ts					
	V render vue		name: t(dtutter))			
	T8 routests					
	> OUTLINE					
			name: t("管理员用户")			
	> 118N ALLY					
1 1	22.4.0 Ma du a 12.274					A

4. 新增新语言

目前项目自带的语言只有 zh 和 en 两种。

4.1. 新增语言文件

在 src/language 目录下增加对应语言文件的 json 文件即可,并在该目录下的 index.js 文件中引入并使用文件。



4.2. 新增语言选择

在 src/layouts/componnets/settingsMobile.vue 中给 webLanguageOptions 国际化数组添加对应的语言类型。



至此新增新语言步骤就结束了。启动项目,选择新增语言,页面内容就会自动显示对应语言文字信息。