

Mysql数据库 workflow 项目适配

流程管理工程配置修改

修改流程管理工程 processAdmin 配置文件

项目工程目录: `risenet-y9boot-webapp-processadmin/src/resources/application.yml`

修改数据源连接池配置

```
spring:
  datasource:
    druid:
      filter:
        wall:
          #关闭Druid防御SQL注入攻击的wallFilter, 不然无法操作数据库
          enabled: false
      y9-public:
        #修改为mysql驱动类名称
        driver-class-name: com.mysql.cj.jdbc.Driver
        #修改为mysql连接池url
        url: jdbc:mysql://localhost:3306/y9_public?
serverTimezone=GMT%2B8&nullCatalogMeansCurrent=true&useUnicode=true&characterEnc
oding=utf-
8&rewriteBatchedStatements=true&useCompression=true&useSSL=false&allowPublickeyR
etrieval=true
        #修改为在mysql默认的超级用户
        username: root
        #修改为在mysql创建的用户密码
        password: '111111'
      flowable:
        driver-class-name: com.mysql.cj.jdbc.Driver
        url: jdbc:mysql://localhost:3306/y9_flowable?
serverTimezone=GMT%2B8&nullCatalogMeansCurrent=true&useUnicode=true&characterEnc
oding=utf-
8&rewriteBatchedStatements=true&useCompression=true&useSSL=false&allowPublickeyR
etrieval=true
        username: root
        password: '111111'
  jpa:
    #修改为mysql版本对应的方言
    database-platform: org.hibernate.dialect.MySQL8Dialect
    properties:
      hibernate:
        #修改为mysql版本对应的方言
        dialect: org.hibernate.dialect.MySQL8Dialect
```

事项管理工程配置修改

修改事项管理工程itemAdmin配置文件

项目工程目录: `risenet-y9boot-webapp-itemadmin/src/resources/application.yml`

修改数据源连接池配置

```
spring:
  datasource:
    druid:
      filter:
        wall:
          #关闭Druid防御SQL注入攻击的wallFilter, 不然无法操作数据库
          enabled: false
      y9-public:
        #修改为mysql驱动类名称
        driver-class-name: com.mysql.cj.jdbc.Driver
        #修改为mysql连接池url
        url: jdbc:mysql://localhost:3306/y9_public?
serverTimezone=GMT%2B8&nullCatalogMeansCurrent=true&useUnicode=true&characterEnc
oding=utf-
8&rewriteBatchedStatements=true&useCompression=true&useSSL=false&allowPublicKeyR
etrieval=true
        #修改为在mysql默认的超级用户
        username: root
        #修改为在mysql创建的用户密码
        password: '111111'
      flowable:
        driver-class-name: com.mysql.cj.jdbc.Driver
        url: jdbc:mysql://localhost:3306/y9_flowable?
serverTimezone=GMT%2B8&nullCatalogMeansCurrent=true&useUnicode=true&characterEnc
oding=utf-
8&rewriteBatchedStatements=true&useCompression=true&useSSL=false&allowPublicKeyR
etrieval=true
        username: root
        password: '111111'
    jpa:
      #修改为mysql版本对应的方言
      database-platform: org.hibernate.dialect.MySQL8Dialect
      properties:
        hibernate:
          #修改为mysql版本对应的方言
          dialect: org.hibernate.dialect.MySQL8Dialect
```

工作办件工程配置修改

修改工作办件工程flowableUI配置文件

项目工程目录: `risenet-y9boot-webapp-flowableui-position/src/resources/application.yml`

修改数据源连接池配置

```
spring:
  datasource:
    druid:
```

```
filter:
  wall:
    #关闭Druid防御SQL注入攻击的wallFilter, 不然无法操作数据库
    enabled: false
y9-public:
  #修改为mysql驱动类名称
  driver-class-name: com.mysql.cj.jdbc.Driver
  #修改为mysql连接池url
  url: jdbc:mysql://localhost:3306/y9_public?
serverTimezone=GMT%2B8&nullCatalogMeansCurrent=true&useUnicode=true&characterEnc
oding=utf-
8&rewriteBatchedStatements=true&useCompression=true&useSSL=false&allowPublicKeyR
etrieval=true
  #修改为在mysql默认的超级用户
  username: root
  #修改为在mysql创建的用户密码
  password: '111111'
jpa:
  #修改为mysql版本对应的方言
  database-platform: org.hibernate.dialect.MySQL8Dialect
  properties:
    hibernate:
      #修改为mysql版本对应的方言
      dialect: org.hibernate.dialect.MySQL8Dialect
```