

OceanBase数据库环境

流程管理工程配置修改

修改流程管理工程processAdmin配置文件

项目工程目录: `risenet-y9boot-webapp-processadmin/src/resources/application.yml`

修改数据源连接池配置

```
spring:
  datasource:
    druid:
      filter:
        wall:
          #关闭Druid防御SQL注入攻击的wallFilter, 不然无法操作数据库
          enabled: false
      y9-public:
        driver-class-name: com.mysql.cj.jdbc.Driver
        #修改为oceanbase连接池url
        url: jdbc:mysql://obmt5wqwq8ynuyu8.huawei-cn-south-
1.oceanbase.cloud:3306/y9_public
        #修改为在oceanbase创建的账号
        username: risesoft@obmt5wqwq8ynuyu8
        #修改为在oceanbase创建的用户密码
        password: 'RiseSoft88@'
      flowable:
        driver-class-name: com.mysql.cj.jdbc.Driver
        url: jdbc:mysql://obmt5wqwq8ynuyu8.huawei-cn-south-
1.oceanbase.cloud:3306/y9_public
        username: risesoft@obmt5wqwq8ynuyu8
        password: 'RiseSoft88@'
    jpa:
      # oceanbase可用mysql方言适配
      database-platform: org.hibernate.dialect.MySQL8Dialect
      properties:
        hibernate:
          # oceanbase可用mysql方言适配
          dialect: org.hibernate.dialect.MySQL8Dialect
```

事项管理工程配置修改

修改事项管理工程itemAdmin配置文件

项目工程目录: `risenet-y9boot-webapp-itemadmin/src/resources/application.yml`

修改数据源连接池配置

```
spring:
```

```

datasource:
  druid:
    filter:
      wall:
        #关闭Druid防御SQL注入攻击的wallFilter，不然无法操作数据库
        enabled: false
    y9-public:
      driver-class-name: com.mysql.cj.jdbc.Driver
      #修改为oceanbase连接池url
      url: jdbc:mysql://obmt5wqwq8ynuyu8.huawei-cn-south-
1.oceanbase.cloud:3306/y9_public
      #修改为在oceanbase创建的账号
      username: risesoft@obmt5wqwq8ynuyu8
      #修改为在oceanbase创建的用户密码
      password: 'RiseSoft88@'
    flowable:
      driver-class-name: com.mysql.cj.jdbc.Driver
      url: jdbc:mysql://obmt5wqwq8ynuyu8.huawei-cn-south-
1.oceanbase.cloud:3306/y9_public
      username: risesoft@obmt5wqwq8ynuyu8
      password: 'RiseSoft88@'

jpa:
  # oceanbase可用mysql方言适配
  database-platform: org.hibernate.dialect.MySQL8Dialect
  properties:
    hibernate:
      # oceanbase可用mysql方言适配
      dialect: org.hibernate.dialect.MySQL8Dialect

```

工作办件工程配置修改

修改工作办件工程flowableUI配置文件

项目工程目录: `risenet-y9boot-webapp-flowableui-position/src/resources/application.yml`

修改数据源连接池配置

```

spring:
  datasource:
    druid:
      filter:
        wall:
          #关闭Druid防御SQL注入攻击的wallFilter，不然无法操作数据库
          enabled: false
      y9-public:
        driver-class-name: com.mysql.cj.jdbc.Driver
        #修改为oceanbase连接池url
        url: jdbc:mysql://obmt5wqwq8ynuyu8.huawei-cn-south-
1.oceanbase.cloud:3306/y9_public
        #修改为在oceanbase创建的账号
        username: risesoft@obmt5wqwq8ynuyu8
        #修改为在oceanbase创建的用户密码
        password: 'RiseSoft88@'

    jpa:

```

```
# oceanbase可用mysql方言适配
database-platform: org.hibernate.dialect.MySQL8Dialect
properties:
  hibernate:
    # oceanbase可用mysql方言适配
    dialect: org.hibernate.dialect.MySQL8Dialect
```